

WINNIE-WW-C

~65° wide beam with holder C compatible with LEDiL HEKLA


TECHNICAL SPECIFICATIONS:

Dimensions	Ø 49.8 mm
Height	19.3 mm
Fastening	socket
Colour	black
Box size	
Box weight	0 kg
Quantity in Box	364 pcs
ROHS compliant	yes ⓘ











MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour
WINNIE-WW	Lens	PMMA	clear
WINNIE-HLD-C	Holder	PC	black





PHOTOMETRIC DATA (MEASURED):

<p>bridgelux.</p> <p>LED VERO13</p> <p>FWHM 56.0°</p> <p>Efficiency 80 %</p> <p>Peak intensity 0.830 cd/lm</p> <p>Required components: C16142_HEKLA-SOCKET-K</p>		
<p>bridgelux.</p> <p>LED VERO18</p> <p>FWHM 59.0°</p> <p>Efficiency 78 %</p> <p>Peak intensity 0.750 cd/lm</p> <p>Required components: LEDiL: C16142_HEKLA-SOCKET-K</p>		
<p>bridgelux.</p> <p>LED Vesta TW 13mm (25W)</p> <p>FWHM 53.0°</p> <p>Efficiency 79 %</p> <p>Peak intensity 0.890 cd/lm</p> <p>Required components: C16142_HEKLA-SOCKET-K Bender Wirth: 492 Typ L8</p>		
<p>CITIZEN</p> <p>LED CLU LES 4.2mm (HI-Ver.3)</p> <p>FWHM 70.0°</p> <p>Efficiency 84 %</p> <p>Peak intensity 0.650 cd/lm</p> <p>Required components: F15255_HEKLA-SOCKET-C</p>		

PHOTOMETRIC DATA (MEASURED):



CITIZEN

LED CLU700/701
FWHM 70.0°
Efficiency 83 %
Peak intensity 0.650 cd/lm
Required components:
F15255_HEKLA-SOCKET-C





LUMINUS

LED CXM-14
FWHM 60.0°
Efficiency 80 %
Peak intensity 0.760 cd/lm
Required components:
F15859_HEKLA-SOCKET-I





LUMINUS

LED CXM-9
FWHM 66.0°
Efficiency 82 %
Peak intensity 0.680 cd/lm
Required components:
F15255_HEKLA-SOCKET-C



SAMSUNG


LED LC010C G2
FWHM 68.0°
Efficiency 82 %
Peak intensity 0.650 cd/lm
Required components:
F15255_HEKLA-SOCKET-C



PHOTOMETRIC DATA (SIMULATED):




LED V10 Gen7
FWHM 69.0°
Efficiency 83 %
Peak intensity 0.000 cd/lm
Required components:




CITIZEN


LED CLL02x/CLU02x (LES10)
FWHM 68.0°
Efficiency 82 %
Peak intensity 0.000 cd/lm
Required components:



LED CXA/B 13xx
FWHM 72.0°
Efficiency 83 %
Peak intensity 0.000 cd/lm
Required components:



LED CXA/B 15xx
FWHM 70.0°
Efficiency 84 %
Peak intensity 0.000 cd/lm
Required components:



PHOTOMETRIC DATA (SIMULATED):




LED CXA/B 1816 & CXA/B 1820 & CXA 1850

FWHM 65.0°

Efficiency 83 %

Peak intensity 0.000 cd/lm

Required components:



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

Due to use of high power COB's with this product, special attention to proper thermal design is highly recommended. LEDiL has no liability for direct, indirect or consecutive damages arising from the LEDiL products being used outside of the recommended temperature range.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

www.ledil.com/where_to_buy

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

www.ledil.com/where_to_buy