

## Features:



- D-Ring fastening is ideal for bundling trays and IC tubes
- Adjustable, releasable and reusable - easy to install
- Low charging hook and loop material meets ANSI/ESD S20.20
- Custom sizes available
- Operating Temperature: 300°F (149°C) max
- Melting Temperature: 459°F (237°C)
- Straps should be tested regularly to make sure they retain their ESD properties
- Made in America



<a href="#">35653</a>	Low Charging Cable Tie, Non-Stretch D-Ring, 3/4 in (19 mm) x 18 in (457 mm)
<a href="#">35654</a>	Low Charging Tie, Non-Stretch D-Ring, 3/4 in (19 mm) x 20 in (19 mm)
<a href="#">35655</a>	Low Charging Cable Tie, Non-Stretch D-Ring, 3/4 in (19 mm) x 24 in (609 mm)
<a href="#">35656</a>	Low Charging Cable Tie, Non-Stretch D-Ring, 3/4 in (19 mm) x 30 in (762 mm)

Specifications and procedures subject to change without notice.



Made in America



# MENDA

## LOW CHARGING CABLE TIES

3651 WALNUT AVE., CHINO, CA 91710  
PHONE: (951) 627-2453 • FAX: (951) 755-8848  
WEBSITE: [MendaTools.com](http://MendaTools.com)

**DRAWING  
NUMBER:**  
35653

**DATE:**  
September  
2012