



SPECIFICATIONS								
WIRING	INPUT		OUTPUT			SHAFT ROTATION FOR VOLTAGE INCREASE	TERMINAL CONNECTIONS FOR INCREASING VOLTAGE AS VIEWED FROM TOP	
	VOLTS	HERTZ	VOLTS	CONSTANT CURRENT LOAD			INPUT	OUTPUT
THREE PHASE WYE	240	60	0-240	120	49.8	CW	4-4-4	B-B-B
			0-280	120	58.1	CW	2-2-2	B-B-B
UNLESS OTHERWISE SPECIFIED, TOLERANCE IS #			UNITS			TITLE: SPEC. CONTROL DRAWING		
DECIMALS			IN [mm]			VARIABLE		
XX .0005			1"			TYPE: 6011E-6Y		
Holes .03			ALL DIMENSIONS APPLY AFTER PLATING			DRAWN BY: TIM RAU		
ANGLES 1°			DATE: 5/20/98			FIRST USED ON: 5/20/98		
DRAFT 1-1/2"			DO NOT SCALE DWG.			CUSTOMER APPROVAL: _____		
MATERIAL:			CHECKER: _____			DATE: _____		
The information and design disclosed herein was originated by and is the property of STACO ENERGY PRODUCTS CO., which reserves all patent, proprietary, design, manufacturing, reproduction, use and sale rights thereto, and to any article disclosed therein except to the extent rights are expressly granted to others. The foregoing does not apply to vendor proprietary parts.			ENGINEER: _____			SCALE: .2=1		
			DATE: _____			CODE IDENT. NO. 83008		
			SCALE: .2=1			DWG. NO. 032-6782		
			SHEET 1 OF 1			DATE: _____		

