

## Specification Sheet

Part Number: T120L9K2



Heavy Duty Cable Tie, 30" Long, UL Rated, 120lb Tensile Strength, PA66, Natural, 50/pkg

|                     |   |
|---------------------|---|
| Article Number      | 111-12419   |
| Type                | T120L   |
| Color               | Natural (NA)  |
| Features & Benefits | <ul style="list-style-type: none"><li>• Heavy-duty design offers higher tensile strength.</li><li>• Buckle feature on head allows excess strap to be tucked away after installation.</li><li>• Bent tail ensures a quick and simple installation.</li></ul> |
| Quantity Per        | bag   |

### Product Description

Heavy-Duty T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. Durable head design guarantees high tensile strength and a low insertion force. The bent tail allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

**Short Description**

Heavy Duty Cable Tie, 30" Long, UL Rated, 120lb Tensile Strength, PA66, Natural, 50/pkg

**Global Part Name**

T120L-PA66-NA

**Minimum Tensile Strength (Imperial)**

120.0

**Minimum Tensile Strength (Metric)**

535.0

**Length L (Imperial)**

30.0

**Length L (Metric)**

760.0

**Identification Plate Position**

none

**Releasable Closure**

No

**Tie Closure**

plastic pawl

**Variant**

Inside Serrated

**Width W (Imperial)**

0.30

**Width W (Metric)**

7.6

**Bundle Diameter Min (Imperial)**

0.20

**Bundle Diameter Min (Metric)**

5.0

**Bundle Diameter Max (Imperial)**

8.85

**Bundle Diameter Max (Metric)**

224.8

|                               |       |
|-------------------------------|-------|
| <b>Thickness T (Imperial)</b> | 0.075 |
|-------------------------------|-------|

**Thickness T (Metric)** 1.9

|                 |                      |
|-----------------|----------------------|
| <b>Material</b> | Polyamide 6.6 (PA66) |
|-----------------|----------------------|

**Material Shortcut** PA66

|                    |             |
|--------------------|-------------|
| <b>US MIL SPEC</b> | SAE-AS33671 |
|--------------------|-------------|

MS3367-6-9

**Flammability**

UL 94 V2

**Halogen free**

Yes

**Operating Temperature (Metric)**

-40°F to +185°F (-40°C to +85°C)

**ROHS Complaint**

Yes

**Certification/Specification WEB**

CAGE Code 53421 UL-ZODZ.E64139

**UL Recognized (US)**

Yes

**UL Listed (US and Canada)**

Yes

**UL Recognized (US and Canada)**

Yes

|                                   |    |
|-----------------------------------|----|
| <b>Package Quantity(Imperial)</b> | 50 |
|-----------------------------------|----|

**Package Quantity (Metric)** 50

**Customs Number** 3926909987

**Weight (Metric)** 11.5