


PIN RECEPTACLES

FOR 1,65 - 2,08 DIAMETER PINS

0395

0395-X-15-XX-07-XX-10-0

Swage mount in 2,44 hole




Basic Part Number	Board Thickness	Length V
0395-1	0,79	1,57
0395-2	1,57	2,39
0395-3	2,39	3,18
0395-4	3,18	3,96
0395-5	4,78	5,56

8016

8016-0-15-XX-07-XX-10-0


Press-fit in 3,33 mounting hole



0350

0350-0-15-XX-07-XX-10-0


Hex press-fit in 3,28±0,05 plated through-hole



0714

0714-0-33-XX-07-XX-10-0


Wire crimp termination. Accepts wire sizes 14 AWG Max. / 16 AWG Min.



0778

0778-0-18-XX-07-XX-10-0


Press-fit in 3,63 mounting hole. Accepts wire sizes up to 14 AWG



9177

9177-0-18-XX-07-XX-10-0


Press-fit in 3,84 mounting hole. Accepts wire sizes up to 16 AWG



5391

5391-0-15-XX-07-XX-10-0


Solder mount in 4,04 min. mounting hole



8837

8837-0-15-XX-14-XX-10-0


Solder mount in 4,04 min. mounting hole



9837

9837-0-15-XX-14-XX-10-0

Solder mount in 4,04 min. mounting hole



SPECIFICATIONS:

Shell Material: Brass Alloy 360, 1/2 Hard

Contact Material: Beryllium Copper Alloy 172, HT

Dimensions: Millimeters

Tolerances On: Lengths: ±0,13

Diameters: ±0,051

Angles: ±2°



ORDER CODE: XXXX - X - XX - XX - XX - XX - 10 - 0

BASIC PART #

SPECIFY SHELL FINISH:

- 01 5,08µm TIN/LEAD OVER NICKEL
- ◆ 80 5,08µm TIN OVER NICKEL (RoHS)
- ◆ 15 0,25µm GOLD OVER NICKEL (RoHS)

SPECIFY CONTACT FINISH:

- 01 5,08µm TIN/LEAD OVER NICKEL
- ◆ 80 5,08µm TIN OVER NICKEL (RoHS)
- ◆ 27 0,76µm GOLD OVER NICKEL (RoHS)

SELECT CONTACT:

#07 or #14 CONTACT (DATA ON PAGE 261)

(For alternate contact choices, see group H on page 248)

