

**General ordering data**

Order No.	1676640000
Part designation	ZDUS
Version	Feed-through terminal, Shield feed-through terminal, Wemid, dark beige, Direct mounting
EAN	4008190462871
Qty.	20 pc(s).

**Product notes**

Product description	The shielding braid from the stripped control cables is soldered to the ZDUS or crimped on with 2.8 x 0.8 mm cable-lug sleeves. The ZDUS can be installed along side of the ZDU 2.5, ZDU 2.5/3 AN, ZDU 4, ZDU 6 and ZTR 2.5.
---------------------	--

**Additional technical data**

Colour of insulating material	dark beige
Connection direction	top
End plate required	Yes
Installation advice	Direct mounting
Insulating material	Wemid
No. of levels	1
Operating temperature range	- 50 °C, + 120 °C
Product family	Z-series
Type of connection	Crimping
UL 94 flammability rating of insulation material	V-0

**Conductors for clamping (rated connection)**

Type of connection	Shield feed-through terminal
Connection direction	top
Solid, min.	0.5 mm <sup>2</sup>
Solid, max.	2.8 mm <sup>2</sup>
Flexible, min.	0.5 mm <sup>2</sup>
Flexible, max.	1.5 mm <sup>2</sup>

**Dimensions**

Width	4.8 mm
Height of lowest version	33.5 mm
Length	83.5 mm

**Approvals**

Approvals institutes

**Classifications**

eClass 4.1	27-14-11-20
eClass 5.0	27-14-11-20
eClass 5.1	27-14-11-20

**Classifications**

**Similar products**

Order No.	Part designation	Version
-----------	------------------	---------