

# DENSI-PAK® BATTERY HOLDERS

- Supports high density packaging on or off board, positions anywhere for easy access to batteries
- Economical design
- Batteries securely held in place to assure a positive connection and maintain a low contact resistance
- Contact springs self-adjust to variations in battery length
- Snap-on cover protects and secures batteries
- Withstands shock and vibration



## SPECIFICATIONS


**Holder:** ABS

**Springs:** Spring Steel, Nickel Plate

**Wires (Red & Black):** 6.0 (150) long, #26 AWG, Tinned, .187 (4.8) end strip UL/CSA1007


"AA"

### Two (2) Cells - 3V



CAT. NO. 2490


### Three (3) Cells - 4.5V



CAT. NO. 2487


"AAA"

### Two (2) Cells - 3V



CAT. NO. 2489

### Three (3) Cells - 4.5V



CAT. NO. 2484

## PLASTIC BATTERY HOLDERS WITH SNAP-ON CONNECTORS

- Features separable "snap-on/snap-off" battery connector (9 Volt type) to assure reliable connections
- Economical design, holders available for two, three or four cells. Wired in series to accept connector (9 Volt type)
- Easily disconnect battery holder from your device - no tools required
- Batteries securely held in place to maintain a positive contact and a low contact resistance
- Battery contact springs self adjust to variations in battery length
- Withstands shock and vibration
- Ideally mates with Keystone 9 Volt battery straps and connectors (Refer to pages 28 - 29)

"AA"


## SPECIFICATIONS

**Holder:** Polypropylene

**Male/Female Contacts:** Brass, Nickel Plate


**Springs:** Spring Steel, Nickel Plate

### Two Cells - 3V




CAT. NO. 2474

### Three (3) Cells - 4.5V



CAT. NO. 2475

### Four (4) Cells - 6V



CAT. NO. 2476